



PA-410R-5G



PA-450R-5G



PA-410R



PA-450R



PA-455R-5G

PA-400R Series

The Palo Alto Networks PA-400R Series consists of ruggedized ML-Powered Next-Generation Firewalls (NGFWs) that bring next-generation capabilities to industrial applications in harsh environments.

The PA-400R Series ruggedized appliances secure industrial and defense networks in a range of harsh environments, such as utility substations, power plants, manufacturing plants, oil and gas facilities, building management systems, and healthcare networks.

The controlling element of the PA-400R Series is PAN-OS[®], the same software that runs all Palo Alto Networks NGFWs. PAN-OS natively classifies all traffic, inclusive of applications, threats, and content, and then ties that traffic to the user regardless of location or device type. The applications, content, and users—the elements that run your business—serve as the basis of your security policies, resulting in an improved security posture and reduced incident response times. PAN-OS embeds machine learning (ML) in the firewall core to provide inline signatureless attack prevention for file-based attacks while identifying and immediately stopping never-before-seen phishing attempts.

Highlights

- World's first ruggedized ML-Powered NGFW.
- Powered by Precision AI[®], a groundbreaking AI-driven engine that analyzes and prevents threats in real time.
- Leader in the 2025 Gartner[®] Magic Quadrant[™] for Hybrid Mesh Firewall.
- Leader in The Forrester Wave[™]: Enterprise Firewall Solutions, Q4 2024.
- Extended operating range for temperature.
- Certified to IEC 61850-3 and IEEE 1613 environmental and testing standards for vibration, temperature, and immunity to electromagnetic interference.
- Supports high availability with active/active and active/passive modes.
- Features silent, fanless design with no moving parts.
- Simplifies deployment of large numbers of firewalls with optional Zero Touch Provisioning (ZTP).
- Managed with Strata[™] Cloud Manager, the industry's first AI-powered unified management and operations solution for network security.

Post-Quantum Cryptography Optimizations

The PA-400R Series is a post-quantum cryptography (PQC)-ready NGFW that helps you achieve quantum-safe security in hardware and software with PAN-OS 12.1. PA-400R Series NGFWs support:

- PQC for PQC SSL/TLS decryption, PQC VPN site-to-site, PQC SSL/TLS Cipher Translation Proxy, and PQC SSL/TLS Service Profile for Management Access to the firewall.
- PQC algorithms, including NIST standards, like ML-KEM, ML-DSA, and SLH-DSA, as well as experimental PQCs, like Classic McEliece, BIKE, HQC, Frodo-KEM, and NTRU-Prime.

For more information, see [Support for Post-Quantum Features](#) in TechDocs.

Prevention of Malicious Activity Concealed in Encrypted Traffic

PA-400R Series NGFWs provide the ability to:

- Inspect and apply policies to SSL/TLS-encrypted traffic (both inbound and outbound), traffic that uses SSLv3, TLSv1.1, TLSv1.2, and TLSv1.3, as well as application protocols SMTP, WebSocket, gRPC, HTTP/1.0, HTTP/1.1, and HTTP/2.
- Decrypt and inspect SSL/TLS sessions with the classical key exchange algorithms RSA, ECDHE, DHE, and post-quantum key exchange standards ML-KEM, HQC, as well as experimental BIKE and Frodo-KEM.
- Let you enable or disable decryption flexibly—based on URL category, source and destination zone, address, user, user group, device, and port—for privacy and regulatory compliance purposes.

Read the [Decryption: Why, Where, and How whitepaper](#) to learn about decryption to prevent threats and secure your business.

Application Identification and Categorization with Full Layer 7 Inspection

App-ID™ identifies and categorizes all applications, on all ports, all the time, with full Layer 7 inspection, supporting the following capabilities:

- Uses advanced techniques, such as protocol decoding, heuristics, and signature matching, to accurately identify applications across the network, regardless of the port, protocol, or encryption methods used. The optional App-ID Cloud Engine (ACE) service provides on-demand App-IDs for SaaS applications.
- Allows for the effective enforcement of security policies tailored to specific applications, by centralizing the identification and control of applications at the firewall level.
- Uses cutting-edge AI techniques to enhance precision in identifying and categorizing AI-powered applications. These techniques ensure that even the most advanced and dynamic applications are accurately recognized and appropriately managed within the network.

For more information, see the [App-ID solution brief](#).

User Security Enforcement

PA-400R Series NGFWs enforce security for users at any location, on any device, while adapting policies based on their activity. They include the ability to:

- **Unify identity and policy enforcement:** Bridge on-premises and cloud identity stores to enforce consistent user-based policies everywhere via the Cloud Identity Engine, and block malicious traffic sources automatically by using IP geolocation.

- **Automate dynamic risk control:** Apply dynamic security actions based on user behavior and risk scores using Cloud Dynamic User Groups (CDUGs)—without depending on directory updates. Also, leverage automated policy recommendations to save time and reduce human error when restricting suspicious activity.
- **Secure credentials:** Prevent credential theft and abuse by enforcing multifactor authentication (MFA) at the network layer for any application, including legacy and nonweb apps, without requiring application changes.

For more information, see the [Cloud Identity Engine solution brief](#).

Unique Approach to Packet Processing

PA-400R Series NGFWs process packets by using a single-pass architecture. Using this approach, the NGFWs are able to:

- Perform networking, policy lookup, application and decoding, and signature matching—for all threats and content—in a single pass. This significantly reduces the amount of processing overhead required to perform multiple functions in one security device.
- Avoid introducing latency by scanning traffic for all signatures in a single pass, using stream-based, uniform signature matching.
- Produce consistent and predictable performance when security subscriptions are enabled (see table 1).

For more information, see the [Single-Pass Architecture solution brief](#).

AI-Powered Unified Management and Operations with Strata Cloud Manager

Manage your PA-400R Series NGFWs with Strata Cloud Manager, which enables you to:

- **Gain complete visibility across your network security estate:** Achieve real-time, comprehensive visibility of your entire network security landscape, including all users, applications, devices, and the most critical threats that need attention through a unified interface.
- **Enable simple and consistent network security lifecycle management:** Manage configuration and policy management across all enforcement points, including SASE, hardware and software firewalls, as well as all security services to ensure consistency and reduce operational overhead.
- **Strengthen security posture in real time:** Leverage AI-powered analysis to detect, resolve, and optimize policy anomalies like shadow and redundant policies and overly permissive or unused rules. Improve your security posture with integrated best practice recommendations and maintain compliance with industry and InfoSec standards.

For more information, see the [Strata Cloud Manager datasheet](#).

Combined NGFW Clustering and High Availability Elements

NGFW clustering optimizes resource usage and increases throughput while maintaining a highly redundant and resilient solution. This solution enables efficient horizontal scaling for highly available networks.

See the [Migrating to NGFW Clustering whitepaper](#) for more information.

Best-in-Class Cloud-Delivered Security Services Powered by Precision AI

PA-400R Series NGFWs provide best-in-class security with Cloud-Delivered Security Services (CDSS). At the heart of our CDSS is Precision AI. Unlike traditional reactive tools, Precision AI empowers your defenses with proactive Threat Detection, inline prevention, and automated response—stopping even the most evasive, never-before-seen attacks before they cause damage. Backed by threat intelligence from our over 70,000 customers globally, our cloud-delivered services continuously learn, adapt, and evolve. Integrated seamlessly with our NGFW and SASE platforms, CDSS delivers unified protection across web, DNS, email, applications, and more—no matter where your users or data reside.

Whether you're navigating hybrid work, embracing cloud transformation, or defending against sophisticated adversaries, CDSS powered by Precision AI gives you the visibility, automation, and confidence to stay ahead.

Advanced Threat Prevention

Palo Alto Networks Advanced Threat Prevention is the industry's first intrusion prevention system (IPS) that stops zero-day, command-and-control (C2) attacks and unknown exploits completely inline. In addition to traditional IPS capabilities, it delivers industry-leading protection against known and unknown threats.

For more information, see the [Advanced Threat Prevention datasheet](#).

Advanced WildFire

Palo Alto Networks Advanced WildFire® is the industry's largest cloud-based malware prevention engine. It protects organizations from highly evasive threats by using patented ML detection engines, enabling automated protections across networks, cloud, and customer application endpoints.

For more information, see the [Advanced WildFire datasheet](#).

Advanced URL Filtering

Advanced URL Filtering analyzes URL strings and web content in real time and classifies them into benign or malicious categories, which can be built into NGFW policies for control of web traffic. It protects against phishing, malware, ransomware, C2 communications, and evasive web-based attacks.

For more information, see the [Advanced URL Filtering datasheet](#).

Advanced DNS Security

Advanced DNS Security delivers real-time protection that instantly blocks sophisticated DNS request and response-based threats—including DNS hijacking, domain generation algorithms (DGA), DNS tunneling, and C2 callbacks. It uses inline, AI-powered detection models to analyze every DNS request and response in real time. These models enable precise identification of never-before-seen malicious domains, DNS tunneling, C2 activity, and network-level DNS hijacking. This powerful first line of defense identifies and stops threats at the DNS layer—whether they originate from outside or inside the network.

For more information, see the [Advanced DNS Security datasheet](#).

Device Security

Palo Alto Networks Device Security delivers a unified, AI-first solution that provides comprehensive protection and monitoring across your entire attack surface. It discovers all connected devices and then identifies and mitigates hidden risks that would otherwise remain invisible or elusive to even the most seasoned InfoSec professionals.

For more information, see the [Device Security solution brief](#).

SaaS Security

Palo Alto Networks SaaS Security delivers broad visibility and real-time control over all SaaS applications, including GenAI apps. Moreover, it provides robust data protection by monitoring and securing the unapproved movement and storage of sensitive data across various SaaS platforms.

For more information, see the [SaaS Security solution brief](#).

AI Access Security

AI Access Security™ empowers organizations to monitor the adoption and usage of sanctioned and unsanctioned GenAI apps. It proactively prevents sensitive data leakage and provides continuous risk monitoring so organizations can safely adopt and use third-party GenAI tools.

For more information, see the [AI Access Security datasheet](#).

Advanced SD-WAN

Easily adopt SD-WAN by simply enabling it on your existing firewalls with integrated security. Get an exceptional end-user experience and ensure SLAs by using SD-WAN path measurements and application steering capabilities to intelligently steer applications to the best performing paths.

For more information, refer to the [SD-WAN documentation](#) in TechDocs.

Integrated 5G Cellular Modem

The integrated 5G Next-Generation Firewall is expanding the entry-level appliance portfolio to include the PA-455R-5G, PA-450R-5G, and the PA-410R-5G, with integrated 5G cellular modem. With this new appliance, enterprise and remote branches can ensure optimal uptime with 5G leveraged as a backup WAN transport for business-critical applications. In addition, other mobile businesses that require cellular as their primary WAN can simply deploy this appliance and ensure rapid deployment without the hassle of adding additional appliances to leverage 5G.

Table 1. PA-400R Series Performance and Capabilities

	PA-410R	PA-410R-5G	PA-450R	PA-450R-5G	PA-455R-5G
Firewall throughput (appmix) [†]	1.4 Gbps	1.4 Gbps	3.2 Gbps	3.2 Gbps	3.2 Gbps
Threat Prevention throughput (appmix) [†]	650 Mbps	650 Mbps	1.7 Gbps	1.7 Gbps	1.8 Gbps
IPsec VPN throughput [‡]	650 Mbps	650 Mbps	1.3 Gbps	1.3 Gbps	1.3 Gbps
Max sessions	64,000	64,000	200,000	200,000	200,000
New sessions per second [§]	11,400	11,400	48,000	48,000	48,000
Virtual systems (base/max)	1/2	1/2	1/2	1/2	1/2
Compliance rating	IP65	IP65	IP40	IP40	IP65

Notes: Results were measured on PAN-OS 12.1

[†] Firewall throughput is measured with App-ID and logging enabled by using appmix transactions.

[‡] Threat Prevention throughput is measured with App-ID, IPS, antivirus, antispymware, WildFire, DNS Security, file blocking, and enabled by using appmix transactions.

[§] IPsec VPN throughput is measured with 64 KB HTTP transactions and logging enabled.

^{||} New sessions per second is measured with application override, using 1 byte HTTP transactions.

^{||} Adding virtual systems over base quantity requires a separately purchased license and a minimum of PAN-OS 11.1.

Table 2. PA-400R Series Networking Features

Interface Modes
L2, L3, tap, virtual wire (transparent mode)
Routing
OSPF v2/v3 with graceful restart, BGP with graceful restart, RIP, static routing
Policy-based forwarding
Point-to-Point Protocol over Ethernet (PPPoE)
Multicast: PIM-SM, PIM-SSM, ICMP v1, v2, and v3
SD-WAN
Path quality management (jitter, packet loss, latency)
Initial path selection (PBF)
Dynamic path change
IPv6
L2, L3, tap, virtual wire (transparent mode)
Features: App-ID, User-ID, Content-ID, WildFire, and SSL decryption
SLAAC
IPsec VPN
Key exchange: manual key, IKEv1, and IKEv2 (preshared key, certificate-based authentication)
Encryption: 3des, AES (128-bit, 192-bit, 256-bit)
Authentication: MD5, SHA-1, SHA-256, SHA-384, SHA-512
PQC VPN
VLANs
802.1Q VLAN tags per device/per interface: 4,094/4,094
Aggregate interfaces (802.3ad), LACP

Table 3. PA-400R Series Hardware Specifications

I/O
PA-410R: 1G RJ45 (4), 1G SFP (2)
PA-410R-5G: Integrated 5G (DSSS – Dual SIM Single Standby), 1G RJ45 (4), 1G SFP (2)
PA-450R: 1G RJ45 (6), 1G SFP/RJ45 combo (2)
PA-450R-5G: Integrated 5G (DSSS – Dual SIM Single Standby), 1G RJ45 (6), 1G SFP/RJ45 combo (2)
PA-455R-5G: Integrated 5G (DSSS – Dual SIM Single Standby), 1G RJ45 (6), 1G SFP/RJ45 combo (2), 1G RJ45 PoE (4)
Management I/O
PA-410R, PA-410R-5G, PA-455R-5G: Management Console Port – RJ45 (1), USB Port for bootstrapping (1), 1G Management Port (1)
PA-450R, PA-450R-5G: Management Console Port – RJ45 (1), USB Port for bootstrapping (1), 1G Management Port (1), micro USB Console Port (1)
Storage Capacity
128 GB
Trusted Platform Module (TPM)
Integrated with TPM for secure boot, hardware root of trust, and securing system secrets.

Table 3. PA-400R Series Hardware Specifications (continued)

Power Supply (Max Power Consumption)	
PA-410R	28.9 W
PA-410R-5G	28.9 W
PA-450R	39.4 W
PA-450R-5G	39.4 W
PA-455R-5G	185 W
Max BTU/hr	
PA-455R-5G: 631 BTU/hr	
PA-450R and PA-450R-5G: 136 BTU/hr	
PA-410R and PA-410R-5G: 129 BTU/hr	
Input Voltage (Input Frequency)	
PA-410R, PA-410R-5G, PA-450R, PA-450R-5G: 12 V–48 VDC (Native DC only products: Optional AC Power adapter is available for purchase)	
PA-455R-5G: 100-240V AC	
Max Current Consumption	
5A @ 12 VDC	
Max Inrush Current	
PA-410R, PA-410R-5G, PA-450R, PA-450R-5G: 5A	
PA-455R-5G: 2A @ 120V AC input	
Dimensions	
PA-410R: 96 mm H x 270 mm W x 208 mm D	
PA-410R-5G: 105 mm H x 270 mm W x 208 mm D	
PA-450R: 44.4 mm H x 390 mm W x 238 mm D – 1RU	
PA-450R-5G: 44.4 mm H x 390 mm W x 253 mm D	
PA-455R-5G: 408.9 mm H x 351.5 mm W x 179.6 mm D	
Weight (Standalone Device/As Shipped)	
PA-410R: 9/12.3 lbs	
PA-410R-5G: 9/12.8 lbs	
PA-450R: 10/14.5 lbs	
PA-450R-5G: 10/14.5 lbs	
PA-455R-5G: 37/57.9 lbs	
Safety	
UL 62368-1:2014, CSA C22.2 No. 62368-1:14, IEC/EN 62368-1: 2014, IEC 62368-1: 2018	
EMI	
FCC Class A, CE Class A, VCCI Class A	
Certifications	
See paloaltonetworks.com/legal-notices/trust-center/compliance	
Environment	
Operating temperature: -40°C to 70°C	
Nonoperating temperature: -40°C to 70°C	
Passive cooling	

Table 4. PA-400R Series Ordering Information

NGFW Model	Part Number (SKU)	Short Description	Included with Base System
PAN-PA-450R and PAN-PA-450R-5G	PAN-1RU-SMALL-ACC	PA-450R and PA-450R-5G Accessory Kit (The accessory kit is included with the base system)	Yes
	PAN-1RU-SMALL-BOX-SET	PA-450R and PA-450R-5G Box set	No
	PAN-1RU-SMALL-PKG-SET	PA-450R and PA-450R-5G Package set	No
	PAN-1RU-SMALL-RACK4	PA-450R and PA-450R-5G 4 post rack mount tray	No
	PAN-1RU-SMALL-WALLMNT	PA-450R and PA-450R-5G wall mount kit	No
	PAN-PWR-180W-AC	PA-450R and PA-450R-5G Spare AC power adapter	No
	PAN-1RU-SMALL-FIPS-KIT	PA-450R and PA-450R-5G FIPS Kit	Yes
PAN-PA-410R and PAN-PA-410R-5G	PAN-PA-410R-ACC	PA-410R and PA-410R-5G Accessory Kit (The accessory kit is included with the base system)	No
	PAN-PA-410R-BOX-SET	PA-410R and PA-410R-5G Box set	No
	PAN-PA-410R-PKG-SET	PA-410R and PA-410R-5G Package set	No
	PAN-PA-410R-FIPS-KIT	PA-410R and PA-410R-5G FIPS Kit	No
	PAN-PA-RGD-DIN-CLIP	PA-410R and PA-410R-5G DIN clip	No
	PAN-PA-RGD-GLND1	Rugged gland kit 1 (1x M20 and 3x M12 glands)	No
	PAN-PA-RGD-GLND2	Rugged gland kit 2 (IP65 SFP Field Install Kit Fiber or CU)	No
	PAN-PA-RGD-GLND-CAP	Rugged gland cap (IP65 SFP Bulkhead Sealing Cap for PA-410R)	No
	PAN-PWR-180W-AC	PA-410R and PA-410R-5G Spare AC power adapter	No
	PAN-PA-410R-FIPS-KIT	PA-410R and PA-410R-5G FIPS Kit	No
PA-455R-5G	PAN-PA-455R-5G-ACC	PA-455R-5G Accessory Kit (The accessory kit is included with the base system)	Yes
	PAN-PA-SERIES-POLE-MOUNT	PA-455R-5G 4 pole mount	No
	PAN-PA-455R-5G-WALL-MOUNT	PA-455R-5G 4 wall mount	No

www.haumoun.com



3000 Tannery Way
 Santa Clara, CA 95054
 Main: +1.408.753.4000
 Sales: +1.866.320.4788
 Support: +1.866.898.9087
 www.paloaltonetworks.com

© 2026 Palo Alto Networks, Inc. A list of our trademarks in the United States and other jurisdictions can be found at <https://www.paloaltonetworks.com/company/trademarks.html>. All other marks mentioned herein may be trademarks of their respective companies.
 strata_ds_pa-400r_022726